

UECONELED840R-BL

About Product

Decorative Beacon, 4000K, 3W, Clear red



Technical Information

Luminaire Name:	Decorative Beacon
accessory Name:	Decorative Beacon
Catalog Code/product code:	UECONELED840R-BL
Mounting Type:	Vertical pole mounting
Application:	Street and Urban lighting
Light source type:	DOB LED (PF> 0.5)
Module/ Lamp quantity:	1
CCT (Color temperature):	4000K - Neutral White
Light source:	LED
Lumen maintenance:	> 100.000 hours
Lumen maintenance factor:	L80
CRI (Color rendering index):	> 80
Power Consumption:	3
IP (Ingress Protection):	IP65
Insulation Class:	Class I
Max. Ambient Temperature:	+55°C
Min. Ambient Temperature:	-40°C
Mains voltage:	220~240 VAC
Voltage Frequency:	50 Hz
Wire / Cable Spec:	PVC flexible wire
Wire cross section:	0.5
Terminal material:	Polyamide
Terminal Spec:	3-Pole (Size: 2.5)
Body Material:	Cast aluminum with high pressure die-cast aluminum ring
Body Coating:	Powder coated

UECONELED840R-BL

Body Color:	Black
RAL:	RAL9005
Diffuser/Glass Material:	Polycarbonate
Diffuser/Glass Characteristic:	UV stabilized
Lens Material:	Clear polycarbonate
Gasket Material:	silicon
Gasket Characteristic:	Resistant to pressure, High thermal resistance
Interior Connection Material:	Galvanized coated
Exterior Connection Material:	Dacromet coated
Packaging type:	Nylon cover and carton
Other Characteristics:	Clear diffuser in red Uniform luminance of diffuser with clear polycarbonate lens
Weight(Kg):	0.7
Dimensions(mm):	Ø118x560