

M587MQ10LED3V40-BL

ARTEMIS ViVo recessed square super comfort downlight, Medium light distribution, Hole dimensions: 10x10cm, 4000K, LED3, 1150 Lumens, 12W, Black



About Product

ARTEMIS modern recessed square super comfort (Darklight) downlight luminaire is designed and manufactured by Mazinoor for modern office and commercial lighting applications. Durability, UV free, excellent visual comfort, energy saving, glare control, environment friendliness, and higher than 80 color rendering index (CRI) are among the highlights of this luminaire.

Technical Information

Cataloge Code/product code:	M587MQ10LED3V40-BL
Mounting Type:	Recessed-Exposed false ceiling, Recessed-Gypsum false ceiling
Application:	Hospitality, Gallery and museum, Office, Shopping centers
Light source type:	LED
Module/ Lamp quantity:	1
CCT (Color temperature):	4000K - Neutral White
Light source:	LED
Lumen maintenance:	> 100.000 hours
Lumen maintenance factor:	L85
CRI (Color rendering index):	> 90
Power Consumption:	12
Luminous Flux:	1150
Efficacy (Im/W):	96
IP (Ingress Protection):	IP43 (Underside)
Insulation Class:	Class II
Ballast/ Driver:	Constant Current Driver (PF> 0.9)
FLICKER:	Flicker Free
Ballast/ driver Spec:	Non-dimmable
Control method options:	DALI, Push, On/Off
Mains voltage:	220~240 VAC±10%
Voltage Frequency:	50/60 Hz
Wire / Cable Spec:	PVC solid wire
Wire cross section:	0.5
Terminal material:	Polycarbonate

© Mazinoor reserves all rights to make changes and improving modifications to product configurations without prior notice. The most up to date data are shown on this website and supercedes any relevant data on prior publications.



M587MQ10LED3V40-BL

ARTEMIS ViVo recessed square super comfort downlight, Medium light distribution, Hole dimensions: 10x10cm, 4000K, LED3, 1150 Lumens, 12W, Black

Terminal Spec:	2 pole (Size: 2.5), Tool free wire connection, Cable looping is possible
Cable Looping:	Yes
Body Material:	Die-Cast aluminum
Body Coating:	Powder coated
Body Color:	Black
RAL:	RAL9005
Body Characteristic:	Specially designed cooling feature
Reflector Material:	Polycarbonate
Reflector Coating:	Vacuum coat
Diffuser/Glass Material:	Polycarbonate
Diffuser/Glass Shape:	Frosted
Diffuser/Glass Characteristic:	Uniform light distribution
Light Distribution:	35 degrees
Clamp Material:	Stainless steel
Clamp Characteristic:	Easy and safe tool free installation of the luminaire
Packaging type:	Nylon cover and carton
Order Option:	Dimmable DALI PUSH driver
Weight(Kg):	0.43
Dimensions(mm):	112x112x96
Luminaire mechanical impact resistance:	-



M587MQ10LED3V40-BL

ARTEMIS ViVo recessed square super comfort downlight, Medium light distribution, Hole dimensions: 10x10cm, 4000K, LED3, 1150 Lumens, 12W, Black

Photometric Graph

Dimensional Drawing

