

M587MQ10LED3V40-BL

ARTEMIS ViVo recessed square super comfort downlight, Medium light distribution, Hole dimensions: 10x10cm, 4000K, LED3, 1150 Lumens, 12W, Black



























About Product



ARTEMIS modern recessed square super comfort (Darklight) downlight luminaire is designed and manufactured by Mazinoor for modern office and commercial lighting applications. Durability, UV free, excellent visual comfort, energy saving, glare control, environment friendliness, and higher than 80 color rendering index (CRI) are among the highlights of this luminaire.

Technical Information

Cataloge Code/product code:	M587MQ10LED3V40-BL
Mounting Type:	Recessed-Gypsum false ceiling, Recessed-Exposed false ceiling
Application:	Hospitality, Gallery and museum, Office, Shopping centers
Light source type:	LED
Module/ Lamp quantity:	1
CCT (Color temperature):	4000K - Neutral White
Light source:	LED
Lumen maintenance:	> 100.000 hours
Lumen maintenance factor:	L85
CRI (Color rendering index):	> 90
Power Consumption:	12
Luminous Flux:	1150
Efficacy (lm/W):	96
IP (Ingress Protection):	IP43 (Underside)
Insulation Class:	Class II
insulation Class.	5.455
Ballast/ Driver:	Constant Current Driver (PF> 0.9)
Ballast/ Driver:	Constant Current Driver (PF> 0.9)
Ballast/ Driver: FLICKER:	Constant Current Driver (PF> 0.9) Flicker Free
Ballast/ Driver: FLICKER: Ballast/ driver Spec:	Constant Current Driver (PF> 0.9) Flicker Free Non-dimmable
Ballast/ Driver: FLICKER: Ballast/ driver Spec: Control method options:	Constant Current Driver (PF> 0.9) Flicker Free Non-dimmable DALI, Push, On/Off
Ballast/ Driver: FLICKER: Ballast/ driver Spec: Control method options: Mains voltage:	Constant Current Driver (PF> 0.9) Flicker Free Non-dimmable DALI, Push, On/Off 220~240 VAC±10%
Ballast/ Driver: FLICKER: Ballast/ driver Spec: Control method options: Mains voltage: Voltage Frequency:	Constant Current Driver (PF> 0.9) Flicker Free Non-dimmable DALI, Push, On/Off 220~240 VAC±10% 50/60 Hz
Ballast/ Driver: FLICKER: Ballast/ driver Spec: Control method options: Mains voltage: Voltage Frequency: Wire / Cable Spec:	Constant Current Driver (PF> 0.9) Flicker Free Non-dimmable DALI, Push, On/Off 220~240 VAC±10% 50/60 Hz PVC solid wire



M587MQ10LED3V40-BL

ARTEMIS ViVo recessed square super comfort downlight, Medium light distribution, Hole dimensions: 10x10cm, 4000K, LED3, 1150 Lumens, 12W, Black

Terminal Spec: Tool free wire connection, Cable looping is possible, 2 pole (Size: 2.5) Cable Looping: Yes Die-Cast aluminum **Body Material:** Powder coated **Body Coating:** Black **Body Color:** RAL: RAL9005 **Body Characteristic:** Specially designed cooling feature Reflector Material: Polycarbonate Reflector Coating: Vacuum coat Diffuser/Glass Material: Polycarbonate Diffuser/Glass Shape: Frosted Uniform light distribution Diffuser/Glass Characteristic: Light Distribution: 35 degrees Clamp Material: Stainless steel Easy and safe tool free installation of the luminaire Clamp Characteristic: Packaging type: Nylon cover and carton Dimmable DALI PUSH driver Order Option: Weight(Kg): 0.43 Dimensions(mm): 112x112x96 Luminaire mechanical impact resistance: -



M587MQ10LED3V40-BL

ARTEMIS ViVo recessed square super comfort downlight, Medium light distribution, Hole dimensions: 10x10cm, 4000K, LED3, 1150 Lumens, 12W, Black

Photometric Graph

Dimensional Drawing

