

M587MQ15LED5V40-BL

ARTEMIS ViVo recessed square super comfort downlight, Medium light distribution, Hole dimensions: 15x15cm, 4000K, LED5, 3300 Lumens, 36W, Black



About Product

ARTEMIS modern recessed square super comfort (Darklight) downlight luminaire is designed and manufactured by Mazinoor for modern office and commercial lighting applications. Durability, UV free, excellent visual comfort, energy saving, glare control, environment friendliness, and higher than 80 color rendering index (CRI) are among the highlights of this luminaire.

Technical Information

Catalog Code/product code:	M587MQ15LED5V40-BL
Mounting Type:	Recessed-Concealed false ceiling, Recessed-Gypsum false ceiling, Recessed-Exposed false ceiling
Application:	Office, Shopping centers, Hospitality, Gallery and museum
Light source type:	LED
Module/ Lamp quantity:	1
CCT (Color temperature):	4000K - Neutral White
Light source:	LED
Lumen maintenance:	> 100.000 hours
Lumen maintenance factor:	L85
CRI (Color rendering index):	> 90
Power Consumption:	36
Luminous Flux:	3300
Efficacy (lm/W):	92
IP (Ingress Protection):	IP43 (Underside)
Insulation Class:	Class II
Ballast/ Driver:	Constant Current Driver (PF> 0.9)
FLICKER:	Flicker Free
Ballast/ driver Spec:	short-circuit protection, Non-dimmable
Control method options:	DALI, Push, On/Off
Ballast/ Driver (Channel quantity):	Single channel
Mains voltage:	220~240 VAC±10%
Voltage Frequency:	50/60 Hz
Wire / Cable Spec:	PVC solid wire

M587MQ15LED5V40-BL

ARTEMIS ViVo recessed square super comfort downlight, Medium light distribution, Hole dimensions: 15x15cm, 4000K, LED5, 3300 Lumens, 36W, Black

Wire cross section:	0.5
Terminal material:	Polycarbonate
Terminal Spec:	2 pole (Size: 2.5), Cable looping is possible. Tool free wire connection
Cable Looping:	Yes
Body Material:	Die-Cast aluminum
Body Coating:	Powder coated
Body Color:	Black
RAL:	RAL9005
Body Characteristic:	Specially designed cooling feature
Reflector Material:	Polycarbonate
Reflector Coating:	Vacuum coat
Diffuser/Glass Material:	Acrylic sheet
Diffuser/Glass Shape:	Clear
Light Distribution:	42 degrees
Clamp Material:	Stainless steel
Clamp Characteristic:	Easy and safe tool free installation of the luminaire
Packaging type:	Nylon cover and carton
Order Option (non-Routine):	Dimmable DALI PUSH driver
Weight(Kg):	0.67
Dimensions(mm):	168x168x127
Luminaire mechanical impact resistance:	-

M587MQ15LED5V40-BL

ARTEMIS ViVo recessed square super comfort downlight, Medium light distribution, Hole dimensions: 15x15cm, 4000K, LED5, 3300 Lumens, 36W, Black

Photometric Graph

Dimensional Drawing

